

## STEAM HOSE



**APPLICATION:** Hose for hot water and saturated steam up to 18 BAR

<b>STANDARD</b>	IS 10655 Type 3/BS 5342
<b>CONSTRUCTION</b>	<p><b>CORE:</b> EPDM rubber resistant high temperature steam</p> <p><b>REINFORCEMENT:</b> Double steel wire braids</p> <p><b>COVER:</b> Black color, EPDM rubber resistant to abrasion, heat and weather</p>
<b>OPERATING TEMP.</b>	Up to +210° C

TECHNICAL  
CHARACTERISTICS

Code	Dash Size	DN	Inner Diameter		Outside Diameter		Working Pressure		Burst Pressure		Minimum Bend	
			mm	inch	mm	inch	bar	psi	bar	psi	mm	inch
92S17RH08	-8	12	12.7	1/2"	23.0	0.91	18	210	180	2600	175	7.0
92S17RH12	-12	20	19.0	3/4"	30.0	1.18	18	210	180	2600	240	9.6
92S17RH16	-16	25	25.4	1"	36.8	1.45	18	210	180	2600	300	12.0
92S17RH20	-20	32	31.8	1.1/4"	43.5	1.71	18	210	180	2600	400	16.0
92S17RH24	-24	38	38.1	1/2"	49.5	1.95	18	210	180	2600	500	20.0
92S17RH32	-32	50	50.8	2"	64.0	2.52	18	210	180	2600	625	25.0
92S17RH40	-40	63	63.0	2.1/2"	83.0	3.26	18	210	180	2600	675	27.0
92S17RH48	-48	76	76.0	3"	98.0	3.85	18	210	180	2600	725	29.0