

LZB-FA100 Glass rotameter					
Model	DN	Flow Range		Parameter	Size
		water (l/h)	air (NI/min)		
LZB-FA100-15	15 (mm)	30-300 l/h	10-100 NI/h	Precision: $\pm 4\%$ Working pressure $\leq 0.8\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length : 260mm
		60-600 l/h	20-200 NI/h		
		80-800 l/h	25-250 NI/h		
LZB-FA100-20	20 (mm)	90-900 l/h	20-200 NI/h	Precision: $\pm 2.5\%$ Working pressure $\leq 0.8\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 340mm
		120-1200 l/h	30-300 NI/h		
		180-1800 l/h	50-500 NI/h		
LZB-FA100-25	25 (mm)	180-1800 l/h	50-500 NI/h	Precision: $\pm 2.5\%$ Working pressure $\leq 0.8\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 340mm
		300-3000 l/h	100-1000 NI/h		
		480-4800 l/h	150-1500 NI/h		
LZB-FA100-32	32 (mm)	480-4800 l/h	200-2000 NI/h	Precision: $\pm 2.5\%$ Working pressure $\leq 0.6\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 340mm
		600-6000 l/h	250-2500 NI/h		
		720-7200 l/h	300-3000 NI/h		
LZB-FA100-40	40 (mm)	1-10 m <sup>3</sup> /h	18-180 Nm <sup>3</sup> /h	Precision: $\pm 2.5\%$ Working pressure $\leq 0.6\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 340mm
		1.2-12 m <sup>3</sup> /h	20-200 Nm <sup>3</sup> /h		
		1.5-15 m <sup>3</sup> /h	25-250 Nm <sup>3</sup> /h		
LZB-FA100-50	50 (mm)	1.2-12 m <sup>3</sup> /h	20-200 Nm <sup>3</sup> /h	Precision: $\pm 2.5\%$ Working pressure $\leq 0.6\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 340mm
		1.5-15 m <sup>3</sup> /h	25-250 Nm <sup>3</sup> /h		
		1.8-18 m <sup>3</sup> /h	30-300 Nm <sup>3</sup> /h		
LZB-FA100-65	65 (mm)	1.8-18 m <sup>3</sup> /h	25-250 Nm <sup>3</sup> /h	Precision: $\pm 1.5\%$ Working pressure $\leq 0.4\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 390mm
		3-30 m <sup>3</sup> /h	35-350 Nm <sup>3</sup> /h		
		4-40 m <sup>3</sup> /h	40-400 Nm <sup>3</sup> /h		
LZB-FA100-80	80 (mm)	4-40 m <sup>3</sup> /h	40-400 Nm <sup>3</sup> /h	Precision: $\pm 1.5\%$ Working pressure $\leq 0.4\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 390mm
		5-50 m <sup>3</sup> /h	50-500 Nm <sup>3</sup> /h		
		6-60 m <sup>3</sup> /h	60-600 Nm <sup>3</sup> /h		
LZB-100FA100	100 (mm)	6-60 m <sup>3</sup> /h	60-600 Nm <sup>3</sup> /h	Precision: $\pm 1.5\%$ Working pressure $\leq 0.4\text{Mpa}$ Temp.: - 20 ~ 120 °C	Length: 410mm
		7-70 m <sup>3</sup> /h	70-700 Nm <sup>3</sup> /h		
		10-100 m <sup>3</sup> /h	90-900 Nm <sup>3</sup> /h		

گروه صنعتی متالیکان فارس

Metalicanfars.com