

LZB-VA/WA/FA 30S Series Glass rotameter

Model	DN	Flow Range		Parameter	VA30S (Thread)	FA30S (Flange)	WA30S (Hygiene quick connect)	Size
		Water 20°C (l/h)	Air 101325Pa 20°C (m³/h)					
LZB-VA 30S-15 LZB-FA 30S-15 LZB-WA 30S-15	15 (mm)	10-100 12-120 16-160 20-200 25-250 30-300 36-360 40-400 46-460 63-630 65-650 75-750	0.12-1.2 0.2-2 0.3-3 0.4-4 0.5-5 0.6-6 0.8-8 0.9-9 1.2-12 2-20	Precision: ± 1.5 % Working pressure ≤ 1.0 Mpa Temp.: - 20 ~ +80 °C Body : SS304				VA30S: 344mm FA30S: 348mm WA30S: 376mm
LZB-VA 30S-25 LZB-FA 30S-25 LZB-WA 30S-25	25 (mm)	63-630 80-800 100-1000 120-1200 160-1600 200-2000 250-2500 300-3000	1.6-16 2-20 2.5-25 3-30 4-40 5-50 6-60	Precision: ± 1.5 % Working pressure ≤ 0.9 Mpa Temp.: - 20 ~ +80 °C Body : SS304				VA30S: 348mm FA30S: 348mm WA30S: 376mm
LZB-VA 30S-40 LZB-FA 30S-40 LZB-WA 30S-40	40 (mm)	63-630 80-800 250-2500 300-3000 400-4000 500-5000 600-6000	5-50 6-60 8-80 9-90 12-120	Precision: ± 1.5 % Working pressure ≤ 0.7 Mpa Temp.: - 20 ~ +80 °C Body : SS304				VA30S: 348mm FA30S: 348mm WA30S: 376mm
LZB-VA 30S-50 LZB-FA 30S-50 LZB-WA 30S-50	50 (mm)	250-2500 300-3000 400-4000 500-5000 630-6300 800-8000 1000-10000 1500-15000 4000-16000	10-100 12-120 16-160 20-200 30-300	Precision: ± 1.5 % Working pressure ≤ 0.7 Mpa Temp.: - 20 ~ +80 °C Body : SS304				VA30S: 380mm FA30S: 370mm WA30S: 376mm